

SMARTEX MIRACLE High Speed Washer Extractors

1200-1350-1500-2250-3430-5000 lt

		Miracle 1200	Miracle 1350	Miracle 1500	Miracle 2250	Miracle 3430	Miracle 5000
Drum Volume	(It)	1.125	1.320	1.480	2.280	3.430	4.800
Drum Diameter	(mm)	1.070	1.140	1.240	1.480	1.720	1.720
Drum Depth	(mm)	1.294	1.290	1.255	1.420	1.530	2.120
Washing Speed		Adjustable-Variable					
Max. Extraction	(rpm)	820	790	760	700	645	645
Max. G Force	(G)	400	400	400	400	400	400
Motor Power	(Kw)	18,5	18,5	22	30	18,5	22
Width	(mm)	1.530	1.585	1.750	1.915	2.175	2.200
Depth	(mm)	2.415	2.448	2.480	2.275	2.550	3.650
Height	(mm)	2.030	2.056	2.120	2.530	2.730	2.550
Height in Tilted Position	(mm)	2.370	2.456	2.461	2.845	3.110	3.650
Weight	(kg)	2.230	2.700	2.980	4.530	6.300	7.360
weignt	(kg)	2.230	2.700	2.980	4.530	6.300	



1:2,5-1:3 LIQUOR RATIO dry garments



POLYRIB ECO DRUM SYSTEM

0/050 less water, chemicals, steam and waste water

electric energy



Double **Pump** Circulation & Drain



SPIN WASH SYSTEM

Washing with Spin wash Jet Spraying Technology

Prevents all crease marks, abrassion and undesired mechanical effects.

Sustainable washing technology.



400 G **EXTRACTION FORCE**

%20 less drying energy and time



SMART BALANCING

totally vibration free extraction eliminates the risk of damages









TOLKAR ULTIMATE CONTROL SYSTEM

remote access enables updates of parameters or versions, recipe preparation, upload/download, recipe transfer to desired machines

USB programme and parameter transfer between machines 100 recipes, 100 steps

reporting amount of dyed garments, consumption of water, electric, steam, loading and operating times (Optional)

PLC Controlled

Touchscreen panel





INNER DRUM

SYSTEM

Automatic precision and steam intake in accordance with Automatic Weighing (Optional)

(Optional)

Reporting of Consumptions and productivity

LOADING DOOR

(Optional)

Easy and automatic loading

(Optional)

System Controls And Data Acquisition System

(Optional)