

TOLKAR MIRACLE

Sample Washer Extractor

40 - 100 - 200 - 300 - 400 - 500 - 600 lt

		Miracle 40	Miracle 100	Miracle 200	Miracle 300	Miracle 400	Miracle 500	Miracle 600
Drum Volume	(lt)	40	100	208	300	400	500	600
Drum Diameter	(mm)	420	610	762	762	915	915	1.092
Drum Depth	(mm)	300	345	460	662	610	760	642
Motor Power	(kw)	1,5	1,5	3	4	5,5	7,5	11
Width	(mm)	715	825	990	990	1.180	1.180	1.460
Depth	(mm)	980	860	1.030	1.300	1.345	1.525	1.590
Height	(mm)	1.060	1.190	1.450	1.450	1.780	1.780	2.000
Weight	(kg)	280	350	595	770	1.125	1.230	2.250

1:2,5-1:3
LIQUOR RATIO
dry garments

POLYRIB ECO DRUM SYSTEM
%50 less water, chemicals, steam and waste water | **%40** less electric energy

SPIN WASH SYSTEM
Washing with Spin wash Jet Spraying Technology
Prevents all crease marks, abrasion and undesired mechanical effects.
Sustainable washing technology.

300 G EXTRACTION FORCE

TOLKAR ULTIMATE CONTROL SYSTEM
remote access enables updates of parameters or versions, recipe preparation, upload/download, recipe transfer to desired machines
USB programme and parameter transfer between machines
100 recipes, 100 steps

PLC Controlled
Touch screen panel

Fully Stainless Steel Outer Structure

SINGLE MAIN CHEMICAL INLET TANK



O₃

Suitable for all ozone applications
(Optional)



Smart Bubble suitable for smart flow nano bubbles spray
(Optional)
(All in one)



Suitable for stone washing Applications with reinforced construction



Cyclone filter for easy stone and lint collection



316 L
3+3 mm
removable
drum



AUTOMATIC WEIGHING SYSTEM
Automatic precision of water, chemical and steam intake in accordance with Automatic Weighing System
(Optional)



AUTO REPORT
Reporting of Consumptions and productivity
(Optional)



SCADA
System Controls And Data Acquisition System
(Optional)